



WZY-A7808LC/TA/TB

全自动上料8轴包胶绕线机

Automatic Loading 8 Spindle Taping and Winding Machine



Features

产品特点

- ✓ 机器关键零部件全部采用日本、德国、台湾进口品牌，可靠性强，耐用度高，保障机器使用寿命；
Key components are Japanese, German or Taiwan Brand, high reliability and durability, greatly prolonged the machine lifetime
- ✓ 使用精密带反张力控制张力器，使产品排线更整齐；
Use precision tensioner with backward tension control to achieve better wire alignment
- ✓ 采用独立式包胶装置，胶带宽窄兼容，可实现不断胶带层间隔离、收直角，且包胶平整，并能实现两边档墙胶带≤1圈；
Adopt independent taping device, compatible for different size tape, can achieve layer isolation without tape break, straight angle and neat taping performance, Both sides margin taping ≤1 turn is achievable
- ✓ 上下料装盘同一工位时进行（空骨架、成品）；
Bobbin loading and finished parts plating share the same station at the same time (bobbin, finished parts)
- ✓ 具有自动夹线、断线、排除废线功能。
With wire auto holding, breaking and removing function

Parameter

技术参数

| 型号 Models | WZY-A7808LC/TA/TB |
|-----------------------------|---|
| 绕线轴距 Spindle Pitch | 78mm |
| 轴数 Spindle Numbers | 8 |
| 主轴速度 Spindle Speed | 8000rpm |
| 主轴马达功率 Spindle Motor | 1500W |
| 三维马达功率 XYZ Spindle Motor | 400W |
| 适用线径 Wire Range | 0.025~0.5mm (Depending on each tensioner's configuration) |
| 最大骨架外径 Max.Bobbin OD | 50mm |
| 快速夹具接口内径 Jig Inner Diameter | 10mm |
| 电源 Power Voltage | AC 220V±10% |
| 总功率 Power | 6000W |
| 空气压力 Air pressure | 0.4~0.6mpa |
| 机器尺寸 Machine Size | 2850*1450*1850mm |
| 机器重量 Machine Weight | ~1100kgs |